

IP CCTV / Counting and Capacity Control / People Counting Cameras

DS-2CD6825G0/C-IS(2mm)(B)

HIKVISION



Features

- Hikvision
- PRO Range
- IP People Counter Camera
- Double sensor
- 1/2.7" Progressive Scan CMOS
- 1080p (1920x1080)
- 2 mm Lens
- 0 Lux
- IR Range 6 m
- Compression H.265+ / H.265 / H.264+ / H.264
- 3D DNR
- Integrated microphone
- Alarms
- Audio
- Displays on screen the count of entries, exits and transit
- RJ-45 10/100M BaseT
- PoE IEEE802.3af
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible
- Suitable for interior

- 
- Ceiling installation

Specifications

Brand	HIKVISION
Range	PRO
Image sensor	1/2.7" Progressive Scan CMOS
Maximum resolution	1080p (1920x1080)
Main Stream rate	25 fps (1920x1080, 1280x720)
Extra Stream rate	25 fps (704x576, 640x480)
Compression	H.265+ / H.264+ / H.265 / H.264
Bitrate	32 Kbps ~ 16 Mbps
Electronic Shutter	1/25~1/100.000 s
Lens	2 mm
Viewing Angle (FOV)	H: 104.5°, V: 70.5°, D: 112°
Minimum illumination	Colour: 0.005 Lux @(F1.2, AGC ON) 0 Lux with IR range 6 m
Day/Night	Removable mechanical ICR filter
Image improvements	DWDR, BLC, HLC, 3D-DNR, ROI, Mirror function, Privacy masking
Motion Detection	Yes
People counting	Statistics of entries, exits and transit Daily, weekly, monthly and annual reports Supports target filtering by height Installation height: 2.1 m Detection area: 0.95 m Installation height: 2.6 m Detection area: 2.15 m Installation height: 3.1 m Detection area: 3.34 m Installation height: 3.6 m Detection area: 4.53 m Installation height: 4.1 m Detection area: 5.36 m Installation height: 4.7 m Detection area: 5.72 m Installation height: 5.1 m Detection area: 6.08 m Installation height: 5.6 m Detection area: 6.97 m Installation height: 6.0 m Detection area: 7.69 m
Recommended Installation	
Internal memory	Does not have

Alarms	1 input / 1 relay
Audio	1 input / 1 output Integrated microphone
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM
Audio bit rate	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-160Kbps(MP2L2)
Network interface	Ethernet 10/100M BaseT
Remote access	Web Browser, Hik-Connect Smartphone App, PC Software iVMS-4200 and Hik-Central
Interoperability	ONVIF, ISAPI
Power	DC 12 V / 660 mA / 8 W max. / IEEE802.3af PoE
Degree of protection	Suitable for interior
Material	Cover: Plastic Body: Metallic
Temp. operation	-30° C ~ +45° C
Dimensions	36 mm (H) x 168 mm (W) x 61 mm (D)
Weight	435 g