

Analogue CCTV / HD 4in1 / Cameras / Dome Cameras

DS-2CE79H0T-IT3ZF(2.7-13.5mm)(C)

HIKVISION



Features

- Hikvision
- VALUE range
- HDTVI, HDCVI, AHD and CVBS Dome Camera
- High Performance CMOS
- 5 Megapixel (2560x1944)
- Output 4in1
- 2.7~13.5 mm Varifocal Motorised Lens
- 0 Lux
- Smart IR Range 40 m
- 2D DNR
- IR Cut
- Weatherproof IP67

Specifications

Brand	Hikvision
Range	Value
Image sensor	5Mpx CMOS
Maximum resolution	5 Megapixel (2560x1944) to 20 fps
Resolution	TVI: 5Mpx (20 fps), 4Mpx (25~30 fps), 1080p (25~30 fps) CVI: 4Mpx (25~30 fps) AHD: 5Mpx (20 fps), 4Mpx (25~30 fps) CVBS: PAL/NTSC
Lens	2.7~13.5 mm Varifocal Motorised Lens
Viewing Angle (FOV)	95~26° (H), 72~20° (V), 126~33° (D)
Minimum illumination	0.01 Lux @ (F1.2, AGC ON)
Infrared lighting	0 Lux / (Smart IR Range 40 m)
Day / Night	Auto / Color / Black & White (ICR)
Video output	1 x switchable BNC HDTVI, HDCVI, AHD and CVBS
Video output switching	Via Switch
Basic functions	OSD menu (remote)
Configurable OSD functions	DWDR, BLC, HLC, 2DNR, AGC, AWB, Smart IR
Communication	HIKVISION-C
Lens Adjustment	3 Axis
Power	DC 12 V / 6.2 W max.
Degree of protection	Weatherproof IP67
Temp. operation	-40° C ~ +60° C
Material	Metallic
Dimensions	Ø 123.87 mm x 110.24 mm (H) x 134.3 mm (D)
Base diameter	Ø base 123.87 mm / Ø entre tornillos 90 mm / 3 tornillos
Weight	555 g