

Access Controls / Hikvision / Standalone

DS-K1T502DBWX-CQR

HIKVISION



Features

- Hikvision
- Stand-alone access control reader
- Identification by MF DESFire card, QR, Bluetooth (only supported with HikCentral and HikConnect Teams), password and/or combinations
- Capacity for 100.000 cards & 300.000 registers
- TCP/IP, WiFi, RS485 and Wiegand communication
- Integrated controller (door sensor, push button and relay)
- Integrated camera, speaker and microphone
- Remote openings from Hik-Connect
- Compatible with software iVMS-4200
- Suitable for exterior IP65
- Anti-vandal IK09

Specifications

Brand	Hikvision
Model	DS-K1T502DBWX-CQR
Operating system	Linux
Capacity	Up to 100.000 cards/passwords/QR
Records	300.000 registers
Identification modes	Card, PIN, QR quick-read and/or combinations Bluetooth (only supported with HikCentral and HikConnect Teams via APP HikCentral Mobile and APP HikConnect) Dynamic QR (only supported with HikCentral and HikConnect Teams via APP HikCentral Mobile and APP HikConnect)
Proximity card	MF DESFire (13.56 MHz)
Camera	2 Mpx
Communication	TCP/IP, WiFi, RS485 and Wiegand
Integrated controller	Wiegand 26/34, door sensor, pushbutton and relay
Alarms	Tamper, 1 x alarm input, 1 x alarm output
Audio	Bidirectional audio
Special functions	Operation as a video door entry system
Storage	Slot for MicroSD card up to 256 GB
Software	iVMS-4200 / iVMS-4200 AC
Mobile application	Hik-Connect
Power supply	DC 12-24 V / 1 A max.
Degree of protection	Suitable for exterior IP65 Anti-vandal IK09
Temp. operation	-40 °C ~ +70 °C
Dimensions	81 (W) x 177 (H) x 26 (D) mm
Weight	500 g